

TEMPERATURE SENSING DEVICE FOR SELECTIVELY MEASURING
TEMPERATURE AT DESIRED LOCATIONS ALONG AN INTRAVENOUS
FLUID LINE

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of copending U.S. Patent Application Serial No. 09/380,507, filed April 24, 2000, entitled "Method and Apparatus for Pressure Infusion and Temperature Control of Infused Liquids", which is a National Stage Application of PCT International Application No. PCT/US98/04199, filed March 3, 1998, entitled "Method and Apparatus for Pressure Infusion and Temperature Control of Infused Liquids", which claims priority from U.S. Provisional Patent Application Serial Nos. 60/040,885, filed March 3, 1997, entitled "Method and Apparatus for Measurement and Control of Temperature for Infused Liquids" and 60/062,315, filed October 17, 1997, entitled "Method and Apparatus for Pressure Infusion and Temperature Control of Infused Liquids". The disclosures of the foregoing patent applications are incorporated herein by reference in their entireties.

BACKGROUND OF THE INVENTION

Technical Field

The present invention pertains to temperature sensing devices for monitoring temperature of intravenous fluid. In particular, the present invention pertains to temperature sensing devices that monitor the temperature of intravenous fluids at any desirable location along a fluid line (e.g., an intravenous fluid line) to ensure a desired fluid temperature is maintained within the fluid line prior to entering a patient.

Discussion of Related Art

Intravenous (IV) fluids are typically infused within a patient utilizing a liquid filled bag or container and an IV fluid line for delivering fluids under gravity and/or applied pressure from the container to the patient. It is important in many situations that the temperature of the fluid within the IV line be maintained within a desirable and safe temperature range upon entering the patient so as to eliminate any potential for thermal shock and injury to the patient by the fluid.

Accordingly, the related art provides several devices that employ temperature sensors to monitor and/or control the temperature of fluid flowing within an intravenous or other type

1 measures the temperature of the medium flowing through the pipe. An electrical bush part is
2 further secured to the connection piece via a bracket and is connected to the contact pins. The
3 bush part housing includes contact bushes with electrical connecting lines that extend externally
4 of the housing through openings defined therein.

5 U.S. Patent No. 4,138,890 (Brown) discloses a temperature indicating probe including
6 a liquid-in-glass thermometer encased within a housing. The housing includes a series of
7 tapered, cylindrical shaped portions separated by a step or shoulder, which are respectively
8 insertable into variously sized standard medical appliance line openings or fittings, for sensing
9 and indicating the temperature of the working fluids being carried through the line.

10 The related art suffers from several disadvantages. In particular, the Magliochetti et al.
11 and Carter, Jr. et al. systems employ temperature measurement in combination with temperature
12 control, thereby increasing system complexity and costs to employ those systems for temperature
13 measurement functions. Further, the size and/or mounting requirements for those systems tend
14 to restrict system application to particular sections of an IV line. Thus, operators are required
15 to estimate, or adjust system settings to compensate for, conditions at desired IV line sites outside
16 the system application range. This tends to lead to inaccuracies in fluid temperature control and
17 measurement for the desired sites, thereby risking injury to a patient. In addition, the Carter, Jr.
18 et al. system measures temperature for temperature control of fluid without providing any
19 temperature indication to an operator, thereby enabling infusion of fluid of unknown temperature
20 into a patient.

21 The Schaus, Hollweck et al. and Diedrich devices are designed for non-medical fluid
22 systems. Accordingly, these devices are employed for non-sterile applications and are ill-suited
23 for medical applications that require sterility. Although these devices measure fluid temperature,
24 the devices generally do not provide a displayed temperature to an operator. Thus, fluids may
25 attain inappropriate temperatures without notice to the operator which may lead to undesirable
26 conditions or consequences. The Brown device requires an operator to manually observe a
27 thermometer and determine a fluid temperature therefrom. This is distracting to the operator and
28 permits possible operator error to be introduced with respect to the fluid temperature
29 measurement, thereby enabling infusion of fluid at an inappropriate temperature and risking
30 injury to the patient.

31 **OBJECTS AND SUMMARY OF THE INVENTION**

Accordingly, it is an object of the present invention to measure the temperature of a fluid within an IV line via a temperature sensing device selectively securable to a desired site along that line.

It is another object of the present invention to obtain an accurate and reliable temperature indication of fluid within an IV line at any desired location along that line and display the temperature indication to an operator.

Yet another object of the present invention is to removably secure a temperature sensing device to an IV line and facilitate measurement of fluid temperatures at varying locations along that line.

Still another object of the present invention is to facilitate re-use of a temperature sensor with a temperature sensing device to measure the temperature of sterile fluid while maintaining fluid sterility.

A further object of the present invention is to measure and display the temperature of fluid within an IV line via a line fitting employing a temperature sensor coupled to a display device.

The aforesaid objects may be achieved individually and/or in combination, and it is not intended that the present invention be construed as requiring two or more of the objects to be combined unless expressly required by the claims attached hereto.

According to the present invention, a temperature sensing device measures the temperature of a fluid at selected locations along an IV fluid line. The device is secured to a selected portion of the IV line and includes a temperature sensor for measuring fluid flowing within that line. The device is coupled to a temperature display device in communication with the temperature sensor to provide an indication of measured fluid temperature to an operator. The temperature sensing device may include a housing removably secured to a selected portion of the IV line. The housing includes a pivotable lower cover to engage the line and a temperature sensor disposed proximate the engaged line section to indirectly measure fluid temperature. The temperature sensor is coupled to a temperature display device to display the measured temperature to an operator.

Alternatively, the device may be in the form of a holder secured to a selected portion of the IV line. The holder is movable along the line and includes a temperature sensor disposed proximate the line to indirectly measure fluid temperatures at line locations secured to the holder.

1 The temperature sensor is coupled to a temperature display device to display the measured
2 temperature to an operator.

3 The temperature sensing device may alternatively include a housing with upper and lower
4 members pivotally connected to each other and receiving an IV line therebetween. The lower
5 member includes a temperature sensing tip configured to pierce the secured portion of the IV
6 line. The tip directly contacts and measures temperature of fluid within the line, and is coupled
7 to a temperature display device to display the measured temperature to an operator. Further, the
8 temperature sensing device may include a resilient member having a spiral or overlapping
9 configuration to surround a selected portion of the IV line. The resilient member includes a
10 temperature sensing tip configured to pierce the selected IV line portion. The tip directly
11 contacts and measures temperature of fluid within the line, and is coupled to a temperature
12 display device to display the measured temperature to an operator.

13 The temperature sensing device may be in the form of a fitting securable to selected
14 portions of the IV line. The fitting may be a 'T'-type fitting including a fluid conduit and a
15 projection including a thermally conductive receptacle to receive a temperature sensor. The
16 receptacle is disposed in direct contact with the fluid to enable temperature measurement by the
17 temperature sensor. The sensor may alternatively be disposed in direct contact with the fluid
18 (e.g., without employing the receptacle), while a securing mechanism may further be employed
19 to releasably secure the temperature sensor to the fitting. The temperature sensor is coupled to
20 a temperature display device to display the measured temperature to an operator. Alternatively,
21 the fitting may be a 'Y'-type fitting and include a temperature sensor configured in the form of
22 a syringe or needle for insertion into a fitting branch to measure fluid temperature. The sensor
23 is coupled to a temperature display device to display the measured temperature to an operator.
24 The sensor may further be employed with a sheath to permit re-use of the sensor while
25 maintaining fluid sterility.

26 The above and still further objects, features and advantages of the present invention will
27 become apparent upon consideration of the following detailed description of specific
28 embodiments thereof, particularly when taken in conjunction with the accompanying drawings,
29 wherein like reference numerals in the various figures are utilized to designate like components.

30 **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is an exploded front view in elevation and partial section of a temperature sensing device attached to an IV fluid line in accordance with the present invention.

Fig. 2 is a view in perspective of the temperature sensing device of Fig. 1 coupled to a temperature display device for use with an infusion apparatus in accordance with the present invention.

Fig. 3 is a front view in elevation and partial section of a temperature sensing device for an IV fluid line in the form of a holder in accordance with the present invention.

Fig. 4 is a view in perspective of a temperature sensing device including a housing securable to an IV fluid line to measure temperature of fluid therein in accordance with the present invention.

Fig. 5 is a front view in elevation of a locking mechanism of the temperature sensing device of Fig. 4.

Fig. 6 is a view in perspective of a temperature sensing device for an IV fluid line including a spiral or overlapping configuration in accordance with the present invention.

Fig. 7 is a front view in elevation of the temperature sensing device of Fig. 6.

Fig. 8 is a view in perspective of a temperature sensing device for an IV fluid line in the form of a line fitting in accordance with the present invention.

Fig. 9A is an exploded view in perspective of a temperature sensing device in the form of a line fitting and including a thermally conductive receptacle for receiving a temperature sensor in accordance with the present invention.

Fig. 9B is a view in perspective of the thermally conductive receptacle of the temperature sensing device of Fig. 9A.

Fig. 10 is a view in perspective of a temperature sensing device including a securing mechanism in accordance with the present invention.

Fig. 11 is a side view in elevation of the temperature sensing device of Fig. 10.

Fig. 12A is a side view in elevation and section of the securing mechanism of the temperature sensing device of Fig. 10.

Fig. 12B is a bottom view in perspective of the securing mechanism of Fig. 12A.

Fig. 13 is a view in perspective of a temperature sensing device including an alternative line fitting configuration in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A temperature sensing device for measuring the temperature of a fluid within an IV fluid line at operator selected locations along the line is illustrated in Fig. 1. Specifically, a temperature sensing device 2 may be removably affixed around any selected portion of an IV line 30. The device includes a housing member 4 and a cap member 6, wherein each member 6 is typically constructed of an appropriate material (e.g., plastic) having suitable insulative properties to ensure the accuracy of temperatures measured for the portion of a fluid line 8 disposed between the housing and cap members. Housing member 4 has a generally rectangular 9 configuration and includes a channel 10 extending between the longitudinal ends of the housing 10 member and having suitable dimensions to receive a selected portion of fluid line 30 and a 11 temperature sensor 20. However, the housing member may have any geometric configuration 12 suitable for operation of the device as described below. Channel 10 typically includes a sensor 13 receiving area 12, a fluid line receiving area 14 and an open bottom portion defined in a bottom 14 surface 16 of the housing member that provides access to the channel to permit an operator 15 selected portion of IV line 30 to be received within fluid line receiving area 14. Sensor receiving 16 area 12 has a configuration complimentary to temperature sensor 20 to receive and secure the 17 temperature sensor therein. By way of example only, temperature sensor 20 and the sensor 18 receiving area 12 include a generally cylindrical configuration. Fluid line receiving area 14 of 19 channel 10 has a generally rectangular configuration and extends from a lower section of the 20 sensor receiving area. The fluid line receiving area further includes a tapered section that 21 narrows the channel toward bottom surface 16 of the housing member. The tapered section is 22 further dimensioned to frictionally engage and secure the IV line within the device.

Temperature sensor 20 may be implemented by any type of conventional or other 23 temperature sensor (e.g., RTD, IR, NTC, thermistors, thermocouples, etc.) suitable for operation 25 of the device as described below. The temperature sensor may be secured within sensor 26 receiving area 12 of the housing member channel in any suitable manner (e.g., adhesion, 27 frictional engagement, etc.). The temperature sensor is positioned within the sensor receiving 28 area and is disposed proximate and/or in direct contact with the IV line portion disposed within 29 fluid line receiving area 14 to obtain a temperature measurement of fluid within that line.

Cap member 6 is generally rectangular and pivotally connected to the housing member 31 bottom surface to secure a portion of the IV line within channel 10. The cap member basically

1 facilitates insertion and removal of an IV line portion within the channel and may be connected
2 to the housing member via a pin 22. The pin is inserted through a pivotal aperture 24 defined
3 within the cap member toward a cap member front corner (e.g., front left corner as viewed in Fig.
4 1). Pin 22 extends through the cap member and is received within a pin receiving aperture 26
5 that is defined within housing member bottom surface 16 and substantially aligned with aperture
6 24. The pin may be secured within the pin receiving aperture in any suitable manner (e.g.,
7 threaded engagement, adhesion, etc.). The cap member pivotal aperture preferably includes
8 transverse cross-sectional dimensions that are slightly greater than those of the pin to permit
9 rotational movement of the cap member with respect to the pin and the housing member when
10 the pin is secured within pin receiving aperture 26. Alternatively, the housing and cap members
11 may be connected to each other via hinges or any other suitable connection mechanism.

12 The temperature sensing device is typically disposed along IV line 30 of an infusion
13 apparatus as illustrated in Fig. 2. Specifically, the infusion apparatus includes an IV pole 42, a
14 solution bag 40 suspended therefrom and IV line 30 enabling flow of solution from the solution
15 bag to a patient. Sensing device 2 is disposed along line 30 and is in communication with a
16 temperature display or monitor device 50 to provide an operator with indications of fluid
17 temperature measurements at operator selected locations along the IV line. The monitor device
18 may communicate with the fluid device in any suitable manner (e.g., electrical line, RF, IR, etc.).
19 Monitor device 50 typically includes a temperature display 52 (e.g., LED or LCD), a plurality of
20 input devices or buttons 54 and a processor to control monitor device operation and determine
21 fluid temperature based on signals received from the temperature sensing device. The display
22 typically indicates the temperature measured by temperature sensor 20, and may further indicate
23 a desired or set-point temperature entered by the operator via buttons 54. The monitor device
24 may further provide an indication when the temperature measured by sensor 20 falls within a
25 desired range of the set-point temperature. In addition, the monitor device may include a printer
26 and/or data recorder to print and/or record data associated with the measured IV fluid
27 temperature. Exemplary monitor devices for use with the temperature sensing device include a
28 Fluke 50S hand-held thermometer available from Fluke Corporation and a printing thermometer
29 available from Extech Instruments.

30 Operation of the temperature sensing device is described with reference to Figs. 1-2.
31 Initially, an operator rotates cap member 6 with respect to housing member 4 to expose channel

1 10. If temperature sensor 20 is not already disposed within the housing member, the sensor may
2 be inserted and secured within sensor receiving area 12. The temperature sensing device is
3 subsequently secured to IV line 30 by inserting a selected portion of the IV line within fluid line
4 receiving area 14 of housing member channel 10 such that part of the IV line wall frictionally
5 engages the tapered section within the channel. Upon securing the IV line portion within the
6 channel, cap member 6 is maneuvered to secure the IV line within the temperature sensing
7 device. Temperature sensor 20 measures the temperature of fluid within the secured IV line
8 portion and provides temperature measurements to monitor device 50 for display to an operator.
9 The temperature sensing device may further provide temperature measurements of fluid at other
10 locations within the IV line by placing the device at any location along the IV line (e.g., as shown
11 by arrow 60 in Fig. 2) as described above. For example, temperature sensing device 2 may be
12 placed along IV line 30 toward IV solution bag 40 on IV pole 42 or, alternatively, toward the
13 infusion point on the subject (not shown). Thus, the device allows the operator to determine the
14 fluid temperature at any point along the IV line with minimal disruption to the infusion
15 procedure. The temperature sensing device further ensures proper mounting of the temperature
16 sensor with respect to the IV line, thereby enabling a precise temperature measurement of fluid
17 (i.e., not skin or ambient temperature) at specific locations within the IV line. The temperature
18 sensing device may be removed from the IV line by moving cap member 6 with respect to
19 housing member 4 to expose channel 10, and removing the secured portion of IV line 30 from
20 the channel. The temperature sensing device may subsequently be removably attached to and
21 utilized with additional IV lines without compromising sterility of the fluid.

22 A temperature sensing device in the form of a holder is illustrated in Fig. 3. Specifically,
23 device 100 includes a substantially flat rectangular base 102 having curved prongs 104, 106
24 extending away from the base and curving toward each other. A generally rectangular platform
25 112 is attached to base 102 and has dimensions that are greater than those of the base. The
26 platform may include various fastening mechanisms (e.g., hook and loop fasteners, tape, gel, etc.)
27 and may be fastened to a patient (e.g., an arm or other body portion) during temperature
28 measurement along the IV line. Prongs 104, 106 are resilient and may be spread from each other
29 slightly to allow insertion of a portion of the IV line and the temperature sensor therebetween as
30 described below. Prongs 104, 106 each respectively include a longitudinally extending groove
31 114, 116 and a transversely extending projection 108, 110. The grooves are defined in the prongs

FIG. 4-5

1 between projections 108, 110 and base 102, while the projections extend from the distal sections
2 of the respective prongs toward each other. The projections basically serve as a stop to guide the
3 temperature sensor in an appropriate position within device 100.

4 A groove or channel 120 is defined in base 102 and extends in a longitudinal direction.
5 The groove is dimensioned to receive and engage a selected portion of IV line 30. A temperature
6 sensor 124 is dimensioned to be frictionally retained between prongs 104, 106 with sensor
7 portions disposed within grooves 114, 116 and projections 108, 110 serving as a stop for the
8 temperature sensor. The temperature sensor is disposed proximate the IV line portion located
9 within groove 120. Thus, the temperature sensor engages and is in direct contact with the IV line
10 portion disposed within channel 120 to obtain an accurate temperature measurement of the liquid
11 flowing within that IV line portion. The temperature sensor is substantially similar to and
12 functions in substantially the same manner as the temperature sensor described above. In
13 operation, temperature sensor 124 is typically inserted between prongs 104, 106 after insertion
14 of a portion of fluid line 30 within groove 120 of base 102. Placement of the sensor between the
15 prongs allows the device to slide along the IV line while maintaining direct contact between the
16 sensor and the IV line. A temperature display or monitor device (not shown), substantially
17 similar to the monitor device described above, is in communication (e.g., via a wire, RF or IR
18 communication, etc.) with temperature sensor 124 to display temperature of fluid within the
19 secured IV line portion measured by the temperature sensor.

20 The temperature sensing device may provide a direct measurement of fluid temperature
21 within a selected portion of the IV line by puncturing the line with a temperature sensing probe
22 as illustrated in Figs. 4-5. Specifically, temperature sensing device 200 is securable to an
23 operator selected portion of an IV line 230. The device includes a generally rectangular housing
24 201 with an upper member 202 and a lower member 204. The upper and lower members are
25 generally rectangular with rounded corners and are pivotally connected to each other at
26 corresponding sides via a hinge member 205. This allows selective engagement between an
27 internal surface 206 of upper member 202 and an internal surface 208 of lower member 204 as
28 described below. However, the upper and lower members may be connected to each other in any
29 suitable manner to facilitate opening and closing of the housing. The lower and upper members
30 of the housing may be constructed of any suitable rigid materials (e.g., plastic, metal, etc).

1 A generally semi-circular groove 209 is defined within the internal surface of the upper
2 member, while the lower member internal surface includes a generally semi-circular groove 210
3 defined therein in substantial alignment with groove 209. The grooves extend along their
4 respective internal surfaces between the longitudinal ends of the upper and lower members to
5 collectively form a longitudinal channel through the housing when the upper and lower members
6 engage each other. The longitudinal channel is appropriately dimensioned to receive a selected
7 portion of IV line 230 for directly measuring temperatures of fluids flowing within the received
8 IV line portion.

9 A temperature probe 212 is embedded within lower member 204 and extends from
10 groove 210 toward an opposing, external surface of the lower member. Specifically, the probe
11 includes a base 250, supports 252, 254 and a sensing tip 213. Base 250 is substantially
12 cylindrical in the form of a disk and includes supports 252, 254 disposed on the base top surface.
13 The supports are generally semi-circular and each have dimensions less than those of the base
14 in order to reside on the base top surface. Sensing tip 213 is substantially cylindrical including
15 a tapered distal end configured in the form of a spike and dimensions greater than those of the
16 supports. The sensing tip is disposed on the base top surface between supports 252, 254. The
17 supports encompass the sensing tip proximal portion while the tip distal portion extends from
18 the distal ends of the supports through the lower member internal surface and within groove 210.
19 Sensing tip 213 is preferably constructed of stainless steel and is configured to pierce the wall
20 of the IV line when the line is inserted into the housing and the housing is subsequently
21 manipulated to a closed state. Alternatively, sensing tip 213 may project slightly from groove
22 210 to obtain a temperature measurement by contacting (e.g., without piercing) the IV line. The
23 temperature sensing tip may be implemented by any conventional or other type of temperature
24 sensor (e.g., RTD, IR, NTC, thermistor, thermocouple, etc.) for direct measurement of fluid
25 temperatures within the IV line. Sensor wiring 214 is connected to base 250 and extends within
26 lower member 204. The sensor wiring emerges from a side portion of the lower member below
27 hinge member 205 and is coupled to a temperature display or monitor device 217. The sensor
28 wiring transmits signals indicating temperature information from the temperature probe to the
29 monitor device. The monitor device is substantially similar to the monitor devices described
30 above and includes a digital display 218 (e.g., LCD or LED) for displaying measured
31 temperatures and input devices 219 in the form of buttons for controlling temperature values

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31

displayed on the digital display. The monitor device may further print, record or provide indications of temperature measurements as described above.

Locking tabs 220 extend from the upper member internal surface with groove 209 disposed between the tabs. Each locking tab 220 is aligned on internal surface 206 of the upper member with a corresponding generally L-shaped slot 222 defined in the lower member internal surface with groove 210 disposed between the slots. The locking tabs each include a shoulder portion 221 that engages with a lower base or "foot" portion of a corresponding L-shaped slot 222 to maintain the locking tabs within the slots in response to pressing the internal surfaces of the upper and lower members together. Alternatively, device 200 may include any other suitable locking mechanism to releasably or permanently lock the upper and lower members together. Upper member 202 further includes a depression 224 disposed and extending longitudinally on an upper member external surface. Depression 224 is suitably dimensioned to receive a digit of a user's hand (e.g., a thumb or forefinger) and provide an enhanced gripping surface for facilitating closure of the housing by pressing the upper and lower members together upon placement of a portion of an IV line therebetween. The housing may be disposable and configured for a single use, while the temperature probe may be removably disposed within the housing for re-use. In this case, the sensing tip may employ a thermally conductive and disposable cover for each use to maintain fluid sterility.

In operation, upper and lower members 202, 204 are separated from each other such that groove 210 on internal surface 208 of the lower member is exposed. A selected portion of IV line 230 is inserted into groove 210 so as to cover sensing tip 213, and upper member 202 is subsequently pivoted with respect to lower member 204 to align tabs 220 with slots 222. The upper member is pressed against the lower member (e.g., by using depression 224 as a gripping surface for the operator's thumb or forefinger) such that tabs 220 are pressed into slots 222 until shoulders 221 are locked therein. The pressing force of upper member 202 in a direction toward lower member 204 simultaneously forces the portion of IV line 230 disposed between the members toward the lower member internal surface by action of groove 209. This further causes sensing tip 213 to pierce the IV line for direct exposure to IV fluid therein. The sensing tip provides a fluid tight seal between the temperature sensing device and the IV line once the line is pierced. Sensor wiring 214 is subsequently connected to temperature display or monitor device 217 to facilitate display of IV line fluid temperature measured by temperature probe 212.

1 A temperature sensing device of the present invention including a spiral or overlapping
2 configuration is illustrated in Figs. 6–7. Specifically, a temperature sensing device 300 includes
3 a generally cylindrical resilient member 302 including a longitudinal channel 310 defined
4 therethrough. The channel includes dimensions sufficient to receive an operator selected portion
5 of an IV line 330. The resilient member is noncontinuous along its exterior surface and includes
6 an exterior end portion 304 and an opposing interior end portion 306. The exterior and interior
7 end portions overlap, while the resilient member thickness tapers toward the overlapping end
8 portions, thereby forming a narrow gap 308 therebetween. Resilient member 302 is constructed
9 of a resilient material (e.g., plastic) that enables end portions 304, 306 to be separated from each
10 other and facilitate insertion of the IV line within channel 310. A temperature probe 312 is
11 disposed through resilient member 302 and into channel 310. The probe terminates in a sensing
12 tip 313 configured as a spike to pierce the wall of the IV line inserted within the channel. The
13 resilient member has sufficient resiliency to drive the sensing tip through and pierce the line.
14 Alternatively, the resilient member may include a force application mechanism to provide
15 sufficient force to enable sensing the tip to pierce the line. The sensing tip may alternatively
16 obtain a temperature measurement by contacting (e.g., without piercing) the IV line. The
17 temperature probe further includes sensor wiring 314 extending to a temperature display or
18 monitor device 317 for displaying temperatures measured by the probe in substantially the same
19 manner described above. The temperature probe may be implemented by any conventional or
20 other temperature sensors (e.g., RTD, IR, NTC, thermistor, thermocouple, etc.). The monitor
21 device is substantially similar to the monitor devices described above and includes a digital
22 display 318 for displaying measured temperatures and input devices 319 in the form of buttons
23 for controlling temperature values displayed on the digital display. The monitor device may
24 further print, record and/or provide various temperature indications as described above.

25 In operation, end portions 304, 306 are separated to enable insertion of an operator
26 selected portion of IV line 330 within channel 310. The selected IV line portion is inserted
27 between the separated end portions and into gap 308 while device 300 is manipulated (e.g., by
28 rotating resilient member 302 around the IV line) to force the IV line into channel 310. As the
29 IV line enters the channel, sensing tip 313 engages and pierces an exterior surface of the IV line
30 to directly contact fluid therein. Thus, the device functions to retain the sensing tip against the
31 IV line to facilitate temperature measurements of fluid flowing within the IV line. Temperature

1 measurement information is transmitted to monitor device 317 to provide various temperature
2 indications to an operator as described above.

3 A temperature sensing device of the present invention in the form of a fitting securable
4 to an IV line to measure fluid temperature is illustrated in Fig. 8. Specifically, a temperature
5 sensing device 400 includes a fitting 401 including a substantially cylindrical base portion 402
6 and a generally cylindrical projection 406 extending transversely from an intermediate section
7 of the base portion. The base portion includes open ends 404 and a longitudinal channel defined
8 therethrough to permit fluid flow through the base portion. The open ends are securable to
9 selected portions of an IV line 430. The projection similarly includes open ends and facilitates
10 access to the base portion channel. The fitting typically includes a T-type configuration,
11 however, any configuration (e.g., a Y-type fitting, cross fitting, coupling, etc.) may be utilized.
12 Each base portion open end 404 is typically releasably secured to the IV line via a Luer lock 405
13 or any suitable connector, while the fitting is typically disposable after each use to maintain fluid
14 sterility. Alternatively, the fitting may be permanently secured to the IV line (e.g., by welding
15 the ends of the fitting to portions of the IV line) to form a disposable IV line set. The fitting may
16 be constructed of plastic or any other rigid material suitable for use with IV lines.

17 Projection 406 serves to engage and secure a temperature sensor within the fitting.
18 Specifically, a temperature probe 410 is disposed within projection 406 and extends partially
19 within base portion 402. Temperature probe 410 may be implemented by any conventional or
20 other temperature sensor (e.g., RTD, IR, NTC, thermistor, thermocouple, etc.) and may be
21 secured within the projection via any securing mechanisms (e.g., friction fit, adhesives, etc.).
22 The probe is disposed within the projection in a manner that provides a fluid tight seal with the
23 fitting channel to maintain IV fluid within the fitting. Sensor wiring 414 is connected to probe
24 410 and extends from the fitting to a temperature display or monitor device 417. The monitor
25 device is substantially similar to the monitor devices described above and includes a digital
26 display 418 for displaying measured temperatures and input devices 419 in the form of buttons
27 for controlling temperature values displayed on the digital display. The monitor device may
28 further print, record and/or provide various temperature indications as described above.

29 In operation, device 400 is attached to an IV line by securing base portion open ends 404
30 to operator selected portions of IV line 430. Upon securing the fitting to the IV line in a fluid
31 tight relationship, IV fluid is permitted to flow through the IV line and fitting. Sensor wiring 414

1 is connected to temperature monitor 417. Temperature probe 410 contacts fluid flowing through
2 the fitting and directly measures the temperature of the fluid. The probe transmits the measured
3 temperature information via the sensor wiring to the monitor device for display of fluid
4 temperature. Upon completion of an IV fluid temperature measurement or medical procedure,
5 the sensor wiring may be disengaged from the monitor, while the fitting is removed from the IV
6 line and discarded.

7 The temperature sensing fitting may alternatively facilitate releasable engagement of the
8 temperature probe as illustrated in Figs. 9A-9B. Specifically, a sensing device 500 includes a
9 fitting 501 with substantially the same configuration as fitting 401 described above. Fitting 501
10 includes a substantially cylindrical base portion 502 and a generally cylindrical projection 506
11 extending transversely from an intermediate section of the base portion. The base portion
12 includes open ends 504 and a longitudinal channel defined therethrough to permit fluid flow
13 through the base portion. The projection includes open ends and facilitates access to the base
14 portion channel. Base portion open ends 504 are securable to selected portions of an IV line 530
15 via Luer locks 505 or other connectors in substantially the same manner described above for
16 device 400. A thermally conductive receptacle 510 is secured within projection 506 and extends
17 partially within base portion 502 for contacting fluid flowing within the base portion channel.
18 Receptacle 510 may be constructed of stainless steel or any other material having suitable
19 thermal conductivity, and may be secured within the projection via any suitable securing
20 techniques (e.g., friction fit, adhesives, etc.). The receptacle includes a generally cylindrical body
21 520 with a closed distal end that extends partially within the base portion and an open proximal
22 end for receiving a temperature probe 512 as described below. A flange 522 extends radially
23 from the open proximal end of the receptacle to engage an interior surface of the projection. The
24 receptacle includes dimensions sufficient to provide a fluid tight seal between the projection and
25 base portion channel to maintain fluid within the channel. A temperature probe 512 is
26 removably inserted within the receptacle with the distal end of the probe in contact with the
27 receptacle closed end. The probe may be secured within the receptacle via friction fit, a locking
28 or securing mechanism or any other securing techniques. Sensor wiring 514 connects the probe
29 to a temperature display or monitor device 517. The monitor device is substantially similar to
30 the monitor devices described above and displays temperatures measured by temperature probe
31 512 on a digital display 518 in accordance with manipulation of input devices or buttons 519.

1 The monitor device may further print, record and/or provide various temperature indications as
2 described above. The probe may be re-used with new fittings, while the receptacle of each new
3 fitting maintains the sterile field for fluid flowing within that fitting.

4 In operation, device 500 is attached to an IV line by securing base portion open ends 504
5 to selected portions of IV line 530. Upon securing the fitting to the IV line in a fluid tight
6 relationship, IV fluid is permitted to flow through the line and fitting. As fluid flows within the
7 fitting, the receptacle closed end contacts the fluid, while the receptacle conducts thermal energy.
8 Temperature probe 512 is inserted into and contacts the closed end of receptacle 510 to measure
9 the temperature of the receptacle. Temperature signals are transmitted from the probe through
10 sensor wiring 514 to the monitor device for display of fluid temperature to the operator. After
11 completion of an IV fluid temperature measuring or medical procedure, probe 512 is removed
12 from receptacle 510 of the fitting, while the fitting may be discarded. Since the temperature probe
13 does not directly contact fluid flowing within the IV line, the system facilitates repeated use of
14 the probe with additional IV lines without the need for sterilization.

15 The temperature sensing device may employ a securing mechanism for releasably
16 engaging a temperature probe as illustrated in Figs. 10-11 and 12A – 12B. Specifically, a
17 sensing device 600 includes a fitting 601 with substantially the same configuration as fitting 501
18 described above. Fitting 601 includes a substantially cylindrical base portion 602 and a
19 generally cylindrical projection 606 extending transversely from an intermediate section of the
20 base portion. The base portion includes open ends 604 and a longitudinal channel defined
21 therethrough to permit fluid flow through the base portion. The projection includes open ends
22 and facilitates access to the channel. Base portion open ends 604 are securable to portions of an
23 IV line 630 via Luer locks 605 or other connectors in substantially the same manner described
24 above for device 500. A thermally conductive receptacle 610, substantially similar in
25 configuration to receptacle 510 described above, is secured within projection 606 and extends
26 partially within base portion 602 for contacting fluid flowing within the base portion channel.
27 The receptacle includes a generally cylindrical body with a closed distal end that extends
28 partially within the base portion and an open proximal end for receiving a temperature probe 612
29 as described below. A flange 622 extends radially from the open proximal end of the receptacle
30 to engage an interior surface of the projection. The receptacle includes dimensions sufficient to

1 provide a fluid tight seal between the projection and base portion channel to maintain fluid within
2 the channel in substantially the same manner described above.

3 A temperature probe 612 is secured to fitting 601 and disposed within receptacle 610 via
4 a securing member or cap 616. Specifically, cap 616 may be constructed of any suitable
5 materials (e.g., plastic) and includes a generally S-shaped configuration with ends tapering in
6 thickness to facilitate enhanced gripping. The cap includes a channel 624 defined in the cap
7 interior and extending from a cap proximal portion to a cap distal surface. The channel is
8 dimensioned to receive and retain the fitting projection. Temperature probe 612 is disposed
9 within the cap channel and extends beyond the cap distal surface. The channel is dimensioned
10 to receive and retain the fitting projection, while the probe includes transverse cross-sectional
11 dimensions slightly less than those of receptacle 610 to enable insertion of the probe within the
12 receptacle as described below. The cap proximal surface includes a support structure 625
13 disposed thereon to guide sensor wiring 614 and provide structural support for cap 616. Sensor
14 wiring 614 is connected to probe 612 and extends from the probe through the cap proximal
15 surface and support structure 625 to a temperature display or monitor device 617. The monitor
16 device is substantially similar to the monitor devices described above and displays temperatures
17 measured by temperature probe 612 on a digital display 618 in accordance with manipulation of
18 input devices or buttons 619. The monitor device may further print, record and/or provide
19 various temperature indications as described above.

20 Projection 606 further includes tabs 607 disposed toward the projection proximal end and
21 angularly spaced apart by approximately one-hundred eighty degrees. Channel 624 includes
22 transverse cross-sectional dimensions slightly greater than those of the projection, but less than
23 those of the projection portions containing tabs 607. In order to accommodate the projection tab
24 portions, channel 624 includes grooves 615 defined therein and angularly spaced apart by
25 approximately one hundred eighty degrees. The grooves extend from the cap distal surface
26 toward the channel proximal end and include dimensions suitable to accommodate the tabs.
27 Recesses or notches 617 are defined at the proximal ends of the respective grooves and are
28 dimensioned to receive and retain corresponding tabs 607. The transverse cross-sectional
29 dimensions of the projection tab portions are slightly greater than those of the channel with
30 grooves 615, but less than the dimensions of the channel with recesses 617. The grooves
31 basically compress the projection tab portions due to projection resiliency to receive those

1 portions in a snug fashion and to guide the tab portions toward recesses 617. The projection
2 resiliency causes the projection to expand upon reaching recesses 617, thereby forcing tabs 607
3 in a locking engagement with those recesses. Locking of tabs 607 in corresponding recesses 617
4 assures that the temperature probe is positioned in contact with the receptacle within the
5 projection. In addition, grooves 615 may taper in depth toward corresponding recesses 617 to
6 assist in guiding tabs 607 through the grooves and into the recesses.

7 Tabs 607 are each configured to be fractured and removed from the fitting. This prevents
8 the fitting from being re-used for temperature measurement, thereby maintaining fluid sterility.
9 The tabs may be removed from the fitting by rotating the cap with respect to the projection when
10 the tabs are disposed within recesses 617. The recesses inhibit tab motion, thereby enabling the
11 rotational force applied to the cap to fracture and remove the tabs from the fitting. Recesses 617
12 may further be elongated transversely on the cap interior surface to permit initial free rotational
13 movement of cap 616 and enhance application of rotational force to the cap for fracturing the
14 tabs.

15 In operation, temperature device 600 is connected to an operator selected portion of IV
16 line 630 as described above. Securing cap 616 is disposed over fitting projection 606 with
17 temperature probe 612 disposed within the projection and channels 615 aligned with tabs 607.
18 The cap is forced distally onto the projection to allow tabs 607 to travel proximally through
19 channels 615 and be secured within recesses 617, while the temperature probe is inserted into
20 receptacle 610. Upon securing the tabs within the recesses, the cap is effectively locked on the
21 fitting with the temperature probe contacting the interior surface of receptacle 610. Fluid is
22 permitted to flow within the fitting and directly contacts a surface of the receptacle closed end
23 extending within base portion 602. The receptacle conducts thermal energy and the receptacle
24 temperature is measured by the temperature probe and subsequently displayed on the monitor
25 device. Once the temperature measurement or medical procedure is completed, the locking
26 engagement between the cap and fitting may be released by rotating the cap relative to the
27 projection. This causes the tabs to fracture and be removed from the projection, thereby
28 disengaging the cap and temperature probe from the fitting. Thus, device 600 facilitates
29 temperature measurement without direct contact of fluid and employs a temporary locking
30 arrangement between the temperature probe and the fitting, thereby allowing reuse of the probe
31 and securing cap with additional fittings without the need for sterilization. Further, the fitting

1 is limited to a single use for temperature measurement to prevent contamination of sterile fluid.
2 In addition, the tabs may notify an operator of fitting use. Basically, since the securing cap
3 removes the projection tabs after use, the absence of those tabs on the fitting indicates that the
4 fitting has been previously used and may compromise sterile conditions when used for another
5 application.

6 A temperature sensing device in the form of a fitting typically utilized for permitting
7 injection of fluids into an IV line is illustrated in Fig. 13. Specifically, a temperature sensing
8 device 700 includes a fitting 701 with a substantially cylindrical base portion 702 and a
9 generally cylindrical inlet portion 706 extending from, and at an approximate forty-five degree
10 angle relative to, an intermediate section of the base portion. The base and inlet portions each
11 include a longitudinal channel defined therethrough to permit fluid flow through those portions.
12 The fitting inlet portion receives an IV line 730 connected to a fluid source, while the base
13 portion distal end is secured to an IV line 740 for conveyance of fluid to a patient. The fitting
14 may be secured to the IV line portions via locks or connectors in substantially the same manner
15 described above. The fitting typically includes a Y-type configuration, however, any type of
16 fitting configuration may be employed.

17 The proximal section of the base portion includes transverse cross-sectional dimensions
18 greater than those of the base portion distal section and houses a flexible membrane 710. The
19 flexible membrane is constructed of a penetrable nylon or other suitable material that provides
20 a barrier for permitting insertion and removal of a syringe needle or other instrument
21 therethrough, while maintaining a fluid tight seal at the base portion proximal end. A
22 temperature probe 712 is inserted through the membrane and into the fitting to measure the
23 temperature of fluids flowing therein. In particular, probe 712 is configured in the form of a
24 syringe needle and includes a sensing tip 713 disposed at a probe distal end and a handle 715
25 disposed at a probe proximal end. The handle provides a gripping surface for an operator when
26 inserting the sensing tip through the membrane. The temperature probe may be implemented by
27 any conventional or other temperature sensor (e.g., RTD, IR, NTC, thermistor, thermocouple,
28 etc.). Sensor wiring 714 extends from the probe to a temperature display or monitor device 717.
29 The monitor device is substantially similar to the monitor devices described above and displays
30 the measured temperatures on a digital display 718 in accordance with manipulation of input

1 devices or buttons 719. The monitor device may further print, record and/or provide various
2 temperature indications as described above.

3 In operation, fitting 701 is secured to an operator selected portion of an IV line as
4 described above. Temperature probe 712 is inserted through flexible membrane 710 at the base
5 portion proximal end until sensing tip 713 is completely disposed within the fitting and in contact
6 with fluid flowing therein. The probe is connected to the monitor device and fluid temperatures
7 are measured and subsequently displayed as described above. Upon completion of a temperature
8 measurement or medical procedure, the probe may be removed from the fitting and sterilized and
9 reused. Alternatively, device 700 may include a sheath (not shown) constructed of stainless steel
10 or any other suitable thermally conductive material to cover the sensing tip during use. The
11 sheath maintains sterility of the fluid and permits reuse of the sensing tip without sterilization.
12 The sheath may either be discarded or sterilized and reused after completion of a temperature
13 measurement or medical procedure.

14 It will be appreciated that the embodiments described above and illustrated in the
15 drawings represent only a few of the many ways of implementing a temperature sensing device
16 for selectively measuring temperature at desired locations along an intravenous fluid line.

17 The temperature sensing device including the housing and cap members may be of any
18 shape or size and may be constructed of any suitable materials. The device may be secured at
19 any locations along an IV or any other fluid line. The housing and cap members may be of any
20 quantity, shape or size, and may be constructed of any suitable materials. The housing member
21 channel may be of any quantity, shape or size and may be defined within the housing member
22 at any location and extend in any direction. The sensor and fluid line receiving areas may be of
23 any quantity, shape or size, may be defined at any suitable locations and may receive the sensor
24 and fluid line in any manner (e.g., friction fit, securing mechanism, etc.). The cap member may
25 be attached to the housing member via any quantity of any type of fasteners or connectors or in
26 any other manner. The pin and apertures may be of any quantity, shape or size. The apertures
27 may be defined in the housing and cap members at any desired locations. The housing member
28 may further include any suitable locking mechanism to releasably or non-releasably lock the fluid
29 line within the housing member.

30 The temperature sensors or probes of the temperature sensing devices described above
31 may be implemented by any quantity of any type of conventional or other temperature measuring

1 devices (e.g., RTD, IR, NTC, thermistors, thermocouples, etc.). The sensors may be of any
2 shape or size to accommodate a particular application. The temperature display or monitor
3 devices described above may be implemented by any quantity of conventional or other processing
4 devices or circuitry to determine and display fluid temperature. The display devices may include
5 processors and various indicators (e.g., visual, audio, speech synthesis, etc.) to indicate the
6 measured temperature and notify of occurrence of any type of temperature or other conditions.
7 The temperature sensors may communicate with the display devices via any communications
8 medium (e.g., wired, wireless, IR, etc.). The display devices may include any quantity of any
9 type of conventional or other displays (e.g., LCD, LED, etc.) of any size or shape disposed at any
10 suitable locations. The display devices may display any desired information (e.g., time,
11 temperature, date, patient information, etc.), and may be disposed at any locations (e.g., near or
12 away from the temperature sensing device) within view of an operator. The display device may
13 employ any type of input devices (e.g., keypad, buttons, voice recognition, touch screen, etc.) and
14 may further include any types of processing, printing and/or recording devices to process, print
15 and/or record any desired information in any desired fashion.

16 The temperature sensing device in the form of a holder may be of any shape or size and
17 may be constructed of any suitable materials. The base, platform and prongs may be of any
18 quantity, shape or size, may be connected or arranged in any fashion and may be constructed of
19 any suitable materials. The platform may include any quantity of any type of fastening
20 mechanism (e.g., gel, adhesives, hook and loop fasteners, etc.) to secure the holder to any portion
21 of a patient (e.g., arm, leg, etc.). The fastening mechanism may be disposed at any locations on
22 the platform or holder. The grooves defined in the prongs may be of any quantity, shape or size,
23 may be defined at any suitable locations and may extend in any desired direction. The prongs
24 may include any suitable configuration and extend in any desired directions. The prong
25 projections may be of any quantity, shape or size and may be disposed at any suitable locations
26 on the prongs or holder. The base groove may be of any quantity shape or size, may be defined
27 in the base or holder at any desired locations and may extend in any directions. The groove may
28 receive and secure any type of fluid line in any desired manner (e.g., friction fit, securing
29 mechanism, etc.). The holder may include any configuration to secure the temperature sensor
30 and/or fluid line in any desired manner.

1 The temperature sensing device including the upper and lower members may be of any
2 quantity, shape or size and may be constructed of any suitable materials. The upper and lower
3 members may be of any quantity, shape or size and may be constructed of any suitable materials.
4 The upper and lower members may be attached to each other via any type of conventional or
5 other securing mechanism (e.g., hinges, brackets, etc.). The grooves defined in the upper and
6 lower members may be of any quantity, shape or size and may be defined in the members at any
7 desired locations and may extend in any desired directions. The grooves may form a channel of
8 any quantity, shape or size to accommodate any type of fluid line. The temperature sensor may
9 be of any quantity and may be disposed within the upper and/or lower member at any suitable
10 locations. The temperature sensor base and supports may be of any quantity, shape or size and
11 may be constructed of any suitable materials. The sensing tip may be of any shape or size, may
12 be constructed of any suitably thermally conducting materials and may be configured and/or
13 disposed to puncture and/or contact the fluid line to measure fluid temperature.

14 The tabs and slots of the upper and lower members may be of any quantity, shape or size
15 and may be disposed on the upper and lower members at any desired locations. The upper and
16 lower members may include any conventional or other locking mechanism to permanently or
17 releasably secure the members together. The depression may be of any quantity, shape or size,
18 may be disposed at any desired locations on the upper and/or lower members and may receive
19 any quantity of portions of an operator body (e.g., hand, fingers, etc.). A cover may be employed
20 for use with the temperature sensor to maintain fluid sterility and permit re-use of the sensor.
21 The cover may be of any quantity, shape or size and may be constructed of any suitable thermally
22 conducting materials.

23 The temperature sensing device including a spiral configuration may be of any quantity,
24 shape or size and may be constructed of any suitable materials. The device may include any
25 resilient member configured in any fashion to wrap around a fluid line. The channel may be of
26 any shape or size and may extend in any desired direction. The gap between the member ends
27 may include any suitable dimensions. The temperature probe may be disposed on or through
28 the resilient member at any desired locations, while the sensing tip may be of any shape or size,
29 may be constructed of any suitably thermally conducting materials and may be configured and/or
30 disposed to puncture and/or contact the fluid line to measure fluid temperature. The sensing

1 device may include any type of conventional or other force application mechanism (e.g., spring,
2 driving mechanism, etc.) to drive the sensing tip to pierce the fluid line.

3 The temperature sensing device in the form of a line fitting may be of any quantity, shape
4 or size, may be constructed of any suitable materials and may be disposed at any suitable
5 locations along the line. The fitting base and projection may be of any quantity, shape or size and
6 may be constructed of any suitable materials. The base channel may be of any shape or size, may
7 be defined in the base at any locations and extend in any desired directions. The fluid line may
8 be secured to the fitting via any conventional or other locks or connectors. The base and
9 projection may be arranged or connected in any fashion, while the fitting may have any suitable
10 configuration (e.g., T-type fitting, Y-type fitting, cross fitting, coupling, etc.). The fitting may
11 be included within and permanently or releasably connected to a disposable IV line set. The
12 temperature probe may be disposed within the fitting projection in any manner via any
13 conventional or other securing mechanisms (e.g., friction fit, adhesives, clamp, threaded
14 engagement, etc.). The fitting may include a receptacle to maintain fluid sterility and permit re-
15 use of the temperature probe. The receptacle may be of any quantity, shape or size, may be
16 constructed of any suitably thermally conductive materials and may be disposed at any locations
17 within the projection or fitting suitable to contact or thermally conduct heat from fluid flowing
18 within the fitting. The receptacle body and flange may be of any quantity, shape or size and may
19 be constructed of any suitable materials. The temperature probe may be secured within the
20 receptacle via any conventional or other securing techniques (e.g., friction fit, threaded
21 engagement, securing mechanism, etc.). Similarly, the receptacle may be secured within the
22 projection or fitting via any conventional or other securing techniques (e.g., friction fit,
23 adhesives, threaded engagement, securing mechanism, etc.).

24 The securing cap may be of any quantity, shape or size and may be constructed of any
25 suitable materials. The cap channel may be of any shape or size, may be defined at any cap
26 locations and may extend in any desired directions. The temperature probe may be secured
27 within the securing cap via any conventional or other securing techniques (e.g., friction fit,
28 threaded engagement, securing mechanism, etc.). The projection tabs may be of any quantity,
29 shape or size, may be constructed of any desired materials and may be disposed at any locations
30 on the projection or fitting. The channel grooves and notches may be of any quantity, shape or

1 size and may be defined at any locations. The tabs may be secured to the projection or fitting in
2 any manner enabling fracture or removal of the tabs.

3 The temperature sensing device in the form of an injection fitting may be of any quantity,
4 shape or size, may be constructed of any suitable materials and may be disposed at any suitable
5 locations along the line. The fitting base and inlet portions may be of any quantity, shape or size
6 and may be constructed of any suitable materials. The base and inlet portion channels may be of
7 any shape or size, may be defined in the respective portions at any locations and extend in any
8 desired directions. The fluid line may be secured to the fitting via any conventional or other
9 locks or connectors. The base and inlet portions may be arranged or connected in any fashion,
10 while the fitting may have any suitable configuration (e.g., T-type fitting, Y-type fitting, cross
11 fitting, coupling, etc.). The fitting may be included within and permanently or releasably
12 connected to a disposable IV line set. The temperature probe may include any type of
13 configuration, but is preferably in the form of a syringe, needle or other configuration suitable
14 to penetrate the barrier. The membrane or barrier may be constructed of any suitable nylon or
15 other material. The probe sensing tip and handle may be of any shape or size, and may be
16 disposed at any suitable locations on the probe. The temperature probe may be employed with
17 a sheath or covering to maintain fluid sterility and permit re-use of the probe. The sheath may
18 be of any quantity, shape or size and may be constructed of any suitable thermally conducting
19 materials.

20 It is to be understood that the present invention is not limited to the specific
21 configurations or applications described above, and may be utilized to determine the temperature
22 of a fluid at any desired location within a fluid line. For example, the temperature sensors or
23 probes may be embedded within, or entirely or partially wrapped about, the fluid line wall to
24 measure and provide fluid temperature to the monitor device. Alternatively, the temperature
25 sensors or probes may be wrapped entirely or partially about a sensing device or holder, or may
26 be disposed within the fluid line (e.g., attached to the fluid line inner diameter). The temperature
27 sensors and probes may be secured to the fluid line or sensing device or holder via any suitable
28 fastening techniques (e.g., snap type fasteners, adhesives, etc.), and may cover any portion of the
29 fluid line and/or sensing device or holder.

30 The temperature sensing devices described above may be employed with any types of
31 infusion apparatus, such as the apparatus shown in Fig. 2. The temperature sensing devices

1 described above may be placed at any desired locations along a fluid line (e.g., attached to those
2 locations or moved along the fluid line) via any suitable attachment or placement techniques to
3 measure temperature of fluid at those locations. The manners of operation of the temperature
4 sensing devices described above may be modified in any fashion to perform a fluid temperature
5 measurement. A fluid line may include any quantity of temperature sensing devices or
6 corresponding components (e.g., temperature sensors or probes, housings, fittings and/or monitor
7 devices) where temperature measurements may be combined in any fashion (e.g., averaged,
8 weighted, etc.) to determine a fluid temperature.

9 It is to be understood that the terms "top", "bottom", "front", "rear", "side", "height",
10 "length", "width", "upper", "lower" and the like are used herein merely to describe points of
11 reference and do not limit the present invention to any particular orientation or configuration.

12 From the foregoing description, it will be appreciated that the invention makes available
13 a novel temperature sensing device for selectively measuring temperature at desired locations
14 along an intravenous fluid line, wherein a temperature sensing device is selectively secured to
15 an intravenous fluid line at any desired location and provides temperature measurements to a
16 monitor device to display the measured fluid temperature to an operator.

17 Having described preferred embodiments of a new and improved temperature sensing
18 device for selectively measuring temperature at desired locations along an intravenous fluid line,
19 it is believed that other modifications, variations and changes will be suggested to those skilled
20 in the art in view of the teachings set forth herein. It is therefore to be understood that all such
21 variations, modifications and changes are believed to fall within the scope of the present invention
22 as defined by the appended claims.